

Maintenance

CLEANING MATERIALS

The following elements CAN be used:

- Warm water (with 2% of mild soap)
- Sponge
- Cleaning cloth
- Absorbent paper
- Steam cleaners
- Vacuum cleaner



The following elements such as sharp tools (knives, trowels, etc.), steel wool or abrasive sponges, aggressive bath cleaners or solutions for lacquer **must NOT** be used, as they will cause permanent damage to surface area of the unit.

CLEANING OF CONCEALED AREAS

Use a vacuum cleaner to clean the gaskets and chambers between the sashes and frames to remove dust and other foreign matter. Ensure running track, channels and draining holes are clear of debris. A soft brush can be also used for cleaning.

It is recommended to repeat this operation frequently as required.

CLEANING OF FRAMES AND GLASS

Mix 2% soap solution to warm water to clean the frame and glass.

With a soft sponge wash the frames and glass to both inner and outer sides. Afterwards, using a cleaning cloth remove the remaining water drops and soap stains. Finally, with a dry cloth complete the cleaning and dry the frame.

Steam cleaner can also be used instead of soap solution.

It is recommended to repeat this operation monthly for each window section.

MAINTENANCE RECOMMENDATIONS

Yearly:

- Lubricate the stainless steel track, bottom wheel sets and all hinges with silicone based spray lubricant directly applying onto the moving parts.
- Check for loose or missing screws and re-tighten or replace as needed.

KEY OBSERVATIONS

The maintenance for windows should be increased:

- In areas close to highways, coastline or industrial areas.
- In business premises with a higher volume of operation per annum.
- When the doors have not been operated for extended periods of time.